JOURNAL OF GEOSPACE SCIENCE

Vol. 6 No. 1 (2026)

E-ISSN : 2413-6093
https://jogss.org

Remote-Sensing-Driven Monitoring and Change Analysis of Earth Surface Processes: A Comprehensive Analytical Framework

Noah Nordin, Noah Castillo, Noah Baines

Department of Geography, University of Zurich, Zurich, Switzerland

ABSTRACT

The continuous monitoring and analysis of Earth surface processes are fundamental to understanding the complex interactions between anthropogenic activities and natural environmental changes. This comprehensive academic paper explores the theoretical foundations, methodological advancements, and practical applications of remote-sensing-driven analytical frameworks for surface process monitoring. By leveraging multi-temporal, multi-spatial, and multi-spectral satellite imagery, researchers have developed robust methodologies to track land cover transformations, ecological degradation, and cryospheric dynamics. This paper systematically reviews the evolution of Earth observation platforms, detailing the transition from coarse-resolution, single-sensor analyses to high-resolution, multi-sensor fusion paradigms. Furthermore, the discussion provides an extensive examination of contemporary change detection algorithms, emphasizing the integration of time-series analysis and machine learning architectures. Through detailed thematic explorations of urbanization, agricultural phenology, and ecological responses to climate change, the paper evaluates the performance, limitations, and future trajectories of remote sensing applications. The overarching objective is to synthesize current methodologies into a cohesive analytical framework that researchers and policymakers can utilize to derive actionable environmental intelligence. Ultimately, this research underscores the indispensable role of satellite-derived data in fostering sustainable land management and mitigating the impacts of global environmental change..

KEYWORDS

Remote Sensing, Change Detection, Surface Processes, Time-Series Analysis

INTRODUCTION

The Earth system is a highly dynamic entity, characterized by continuous interactions among the biosphere, lithosphere, hydrosphere, and atmosphere. Over the past century, these interactions have been increasingly influenced by human activities, leading to profound transformations in surface processes. Understanding the scale, rate, and spatial distribution of these transformations is critical for managing natural resources, mitigating environmental hazards, and developing sustainable policies. Traditional field-based surveying methods, while highly accurate at local scales, are inherently limited by their spatial constraints, high operational costs, and the logistical challenges associated with accessing remote or hazardous terrains. Consequently, the scientific community has increasingly turned to remote sensing technologies as the primary mechanism for conducting large-scale, systematic observations of the Earth surface. The ability to acquire synoptic, repetitive, and objective data from aerial and orbital platforms has fundamentally revolutionized the environmental sciences, providing researchers with the empirical data necessary to model and analyze complex surface dynamics over extended periods [1]. Remote sensing serves as a non-destructive, macro-level observational tool that captures the electromagnetic radiation reflected or emitted by surface features. The fundamental principle underlying this technology is that different surface materials, such as vegetation, water, soil, and impervious urban structures, exhibit unique spectral signatures across various wavelengths of the electromagnetic spectrum. By utilizing sophisticated sensors mounted on satellites, aircraft, and increasingly, uncrewed aerial vehicles, researchers can quantify these spectral properties and translate them into meaningful geophysical and biophysical variables. This translation process involves complex radiometric calibration, atmospheric correction, and geometric registration, ensuring that the acquired digital numbers accurately represent true surface reflectance. The historical development of remote sensing, particularly the launch of the Landsat program in the early nineteen seventies, marked the beginning of an era of continuous global monitoring. Since then, the proliferation of Earth observation missions has generated vast archives of spatial data, effectively creating a detailed historical record of planetary change [2]. The concept of change detection is central to the remote-sensing-driven analysis of surface processes. Change detection involves the application of multi-temporal datasets to quantitatively analyze the temporal effects of a phenomenon. In the context of Earth observation, this entails identifying differences in the state of an object or phenomenon by observing it at different times. The complexity of change detection arises from the need to differentiate between genuine physical changes on the ground and spurious changes caused by variations in atmospheric conditions, sensor calibration anomalies, illumination geometry, or seasonal phenology. Over the decades, a vast array of mathematical and statistical algorithms has been developed to address these challenges, ranging from simple image differencing and rationing techniques to highly complex machine learning classifications and temporal trajectory modeling. The selection of an appropriate change detection algorithm is highly dependent on the specific surface process being monitored, the characteristics of the available data, and the computational resources at hand. The scope of surface processes monitored via remote sensing is extraordinarily broad, encompassing both gradual trends and abrupt disturbances. Gradual processes, such as the expansion of desertification, the shifting of ecological biomes due to climate change, or the incremental growth of urban peripheries, require long-term, consistent time-series data to accurately model their trajectories. In contrast, abrupt disturbances, such as wildfires, floods, seismic events, or rapid deforestation clearings, demand high-temporal-resolution data to capture the immediate impact and subsequent recovery phases. The integration of data from multiple sensor types, including passive optical radiometers and active microwave synthetic aperture radar systems, has significantly enhanced the scientific capability to monitor these diverse phenomena. Active sensors, in particular, offer the distinct advantage of operating independently of solar illumination and cloud cover, providing vital uninterrupted data streams in tropical and polar regions. As the volume and velocity of Earth observation data continue to grow exponentially, the field is undergoing a paradigm shift towards automated, cloud-based processing

architectures. Platforms that provide petabyte-scale storage and high-performance parallel computing have democratized access to remote sensing data, allowing researchers to conduct global-scale analyses that were previously computationally prohibitive. This technological convergence is facilitating a deeper, more comprehensive understanding of how surface processes respond to both natural forcing and anthropogenic pressures. The following sections of this paper will systematically dissect the components of this analytical framework, exploring the underlying literature, methodological standards, and application domains that define contemporary remote-sensing-driven surface analysis.

2. Literature Review and Background

The literature surrounding remote-sensing-driven monitoring is vast and multidisciplinary, reflecting the technology utility across geology, ecology, urban planning, and climatology. To contextualize the current state of the art, it is necessary to review the historical evolution of Earth observation systems and the corresponding advancements in analytical methodologies.

2.1 Evolution of Earth Observation Systems

The trajectory of remote sensing platforms has been characterized by continuous improvements in spatial, spectral, temporal, and radiometric resolutions. Early satellite missions were primarily designed for coarse-resolution meteorological observations and generalized land cover mapping. The introduction of multispectral scanners revolutionized the field by allowing researchers to view the Earth in multiple discrete bands of the electromagnetic spectrum, particularly the near-infrared region, which is crucial for vegetation analysis. The mid-resolution optical satellites, operating with spatial resolutions of ten to thirty meters, became the workhorse of environmental monitoring. These platforms provided a critical balance between spatial detail and geographic coverage, enabling the creation of regional and global land cover datasets. The longevity and consistency of these mid-resolution programs have allowed scientists to establish baseline environmental conditions and track deviations from these norms over multi-decadal timeframes [3]. In parallel with the evolution of mid-resolution platforms, the demand for finer spatial detail spurred the development of high-resolution commercial satellite systems. These platforms, capable of resolving surface features at the sub-meter level, opened new avenues for detailed urban infrastructure mapping, precision agriculture, and localized environmental assessments. However, the high cost and narrow swath widths of these systems historically limited their application for broad-scale, continuous monitoring. Recently, the deployment of satellite constellations consisting of hundreds of small, relatively inexpensive imaging sensors has addressed the temporal resolution limitations of traditional high-resolution platforms. These constellations can provide daily, or even intra-daily, global coverage, capturing highly dynamic surface processes that would otherwise go unnoticed between the less frequent overpasses of larger flagship satellites. Beyond optical systems, the advancement of active microwave remote sensing, particularly synthetic aperture radar, has fundamentally expanded the observational envelope. Synthetic aperture radar systems transmit microwave pulses towards the Earth and measure the backscattered signal, providing information about the structural and dielectric properties of surface materials. Because microwave radiation penetrates clouds and operates independently of solar illumination, it is indispensable for monitoring regions with persistent cloud cover, such as the equatorial tropics, and for observing polar regions during the long polar night [4]. The interferometric application of synthetic aperture radar, which measures the phase difference between multiple radar acquisitions, has proven uniquely capable of detecting millimeter-scale surface deformations caused by tectonic activity, groundwater extraction, and glacial movement. The integration of optical and active microwave datasets represents a major frontier in remote sensing literature, offering synergistic insights that neither modality could provide independently.

Table 1: Comparison of typical remote sensing platforms used for surface monitoring.

Platform Category	Spatial Resolution	Temporal Resolution	Spectral Range	Primary Application
Coarse Optical	250m to 1km	Daily to Twice Daily	Multispectral	Global vegetation

				trends, sea surface temperature, large-scale climate monitoring
Medium Optical	10m to 30m	5 to 16 Days	Multispectral	Regional land cover mapping, forest disturbance, agricultural monitoring
High-Res Optical	0.3m to 5m	Variable to Daily	Panchromatic, Multispectral	Urban infrastructure mapping, precision agriculture, localized disaster assessment
Active Microwave	1m to 100m	6 to 24 Days	X, C, L, P Bands	All-weather surface structure, deformation monitoring, soil moisture estimation
Hyperspectral	30m to 60m	Variable	Contiguous Narrow Bands	Mineral exploration, precise vegetation health, water quality analysis

2.2 Advances in Change Detection Algorithms

The algorithmic approaches to extracting change information from remote sensing data have evolved significantly, moving from simple visual interpretation and manual digitization to sophisticated, highly automated computational frameworks. Early analytical efforts heavily relied on algebraic operations, primarily image differencing and rationing. Image differencing involves subtracting the pixel values of an image acquired at one date from the corresponding pixel values of an image acquired at a later date. Assuming the data has been rigorously calibrated, a difference value near zero indicates no change, while larger positive or negative values signify significant surface alterations. While computationally efficient, this approach requires the establishment of arbitrary thresholds to distinguish true change from background noise, a process that is often subjective and prone to error [5]. To address the limitations of simple algebraic methods, researchers developed more robust transformation techniques, such as principal component analysis and multivariate alteration detection. Principal component analysis reduces the dimensionality of multi-temporal datasets by projecting the highly correlated spectral bands into a new, orthogonal coordinate system. The minor principal components often capture the localized variance associated with surface changes, isolating these signals from the broader, unchanging environmental background. Similarly, multivariate alteration detection utilizes canonical correlation

analysis to find linear combinations of the multi-temporal bands that exhibit the lowest possible correlation, thereby highlighting areas of maximum change. These transformation techniques offer improved statistical rigor and reduce the reliance on empirical thresholding. Another major paradigm shift in the literature is the transition from pixel-based to object-based image analysis. Traditional pixel-based methods evaluate each spatial resolution cell independently, relying solely on its spectral signature. However, as spatial resolution improved, the internal spectral variability of individual surface features increased, leading to an issue commonly referred to as the salt-and-pepper effect in classification and change detection outputs. Object-based image analysis mitigates this issue by initially segmenting the image into homogeneous, contiguous regions known as objects. These objects correspond to actual landscape features, such as agricultural fields, forest stands, or individual buildings. The change detection algorithms are then applied to the objects rather than individual pixels, incorporating not only spectral information but also spatial characteristics like shape, texture, size, and contextual relationships. This approach significantly improves the accuracy of change detection in highly heterogeneous environments, such as urban and peri-urban landscapes [6].

3. Methodology and Analytical Framework

Establishing a robust methodology for the remote-sensing-driven monitoring of surface processes requires a systematic approach that addresses data acquisition, stringent preprocessing, feature extraction, and temporal analysis. The integrity of the final analytical output is entirely dependent on the rigor applied during the initial data preparation phases.

3.1 Data Acquisition and Preprocessing Standard

The foundation of any remote sensing analysis is the formulation of a comprehensive data acquisition strategy. Researchers must carefully evaluate the specific requirements of the surface process under investigation to determine the optimal spatial, spectral, and temporal parameters of the satellite imagery. For instance, monitoring the rapid progression of a seasonal flood requires high temporal frequency data, potentially sacrificing spatial detail, whereas mapping the slow expansion of urban impervious surfaces necessitates high spatial resolution data acquired at less frequent, perhaps annual, intervals. Furthermore, researchers must account for environmental constraints, specifically cloud cover and seasonal atmospheric variations, which can severely limit the availability of usable optical data. Once the data is acquired, rigorous preprocessing is mandatory to ensure that the images are radiometrically and geometrically consistent across time. Radiometric calibration is the first critical step, converting the raw digital numbers recorded by the sensor into absolute units of physical measurement, specifically at-sensor radiance. This calibration accounts for sensor degradation over time and variations in the operational parameters of the satellite instrument. However, at-sensor radiance is significantly affected by the scattering and absorption of electromagnetic radiation by gases and aerosols in the Earth atmosphere. To derive the true surface reflectance, which is the intrinsic property of the surface materials, complex atmospheric correction models must be applied. These models utilize radiative transfer equations and auxiliary atmospheric data to simulate and remove the atmospheric interference. Without precise atmospheric correction, spurious variations in the data could easily be misinterpreted as actual surface changes [7]. Geometric correction and co-registration are equally critical preprocessing steps. Satellite images are subject to geometric distortions caused by the curvature and rotation of the Earth, the varied topography of the surface, and the viewing geometry of the sensor. Orthorectification corrects these distortions using digital elevation models and ground control points, projecting the image into a standardized map coordinate system. For time-series analysis and change detection, the multi-temporal images must be precisely co-registered to one another. If the pixels from different dates do not perfectly align, a false change signal will be generated along the boundaries of different land cover types. State-of-the-art co-registration algorithms utilize automated image matching techniques to achieve sub-pixel alignment accuracy, which is absolutely essential for monitoring subtle surface modifications.




Figure 1: System architecture of remote Sensing data processing pipeline

Figure 1: System architecture of remote sensing data processing pipeline

3.2 Time-Series Analysis Paradigms

The availability of dense stacks of preprocessed satellite imagery has facilitated the development of advanced time-series analysis paradigms. Rather than comparing two discrete dates, continuous time-series analysis evaluates the entire temporal trajectory of a pixel or object, providing a much deeper understanding of surface dynamics. One of the primary applications of time-series analysis is the monitoring of vegetation phenology. By tracking the variations in vegetation indices, such as the Normalized Difference Vegetation Index, throughout the year, researchers can extract key phenological metrics, including the start of the growing season, the peak of photosynthetic activity, and the onset of senescence. Shifts in these phenological metrics over multiple years serve as sensitive indicators of climate change impacts on terrestrial ecosystems [8]. Beyond seasonal cycles, time-series algorithms are designed to detect various typologies of change, including abrupt, gradual, and cyclical variations. Algorithms such as the Breaks For Additive Season and Trend approach deconstruct the time-series signal into its trend, seasonal, and remainder components. By analyzing the structural changes in these components, the algorithm can precisely identify the timing and magnitude of disturbances, such as clear-cut logging or wildfire events, as well as the subsequent rates of ecological recovery. Similarly, algorithms designed to map vegetation trajectories utilize temporal segmentation techniques to fit piecewise linear models to the spectral data. The vertices of these linear segments represent critical inflection points where the state of the surface transitioned from one trajectory to another, enabling the detailed mapping of forest degradation, agricultural abandonment, and urbanization processes.




Figure 2: Detection of Change Typologies in Time-Series Data

The implementation of continuous time-series analysis is highly resource-intensive, requiring the storage and processing of massive data cubes. Consequently, this methodology has become inextricably linked with the rise of cloud-based geospatial computing platforms. These platforms provide researchers with application programming interfaces to directly access and analyze entire petabyte-scale archives of satellite data without the need to download individual files to local servers. This architecture fundamentally changes the scale at which surface process monitoring can be conducted, transitioning regional studies into continental and global scale analyses.

3.3 Machine Learning Integration

The integration of machine learning and artificial intelligence represents the most significant contemporary advancement in remote sensing methodology. As the volume of data and the complexity

of the desired analytical outputs increase, traditional parametric statistical classifiers are frequently insufficient. Machine learning algorithms, particularly non-parametric models like Random Forests and Support Vector Machines, have demonstrated superior performance in handling the high-dimensional feature spaces typical of multi-temporal and multi-sensor datasets. These algorithms do not assume a normal distribution of the data and are highly capable of modeling the complex, non-linear relationships between spectral signatures and surface land cover classes. Random Forest models operate by constructing an ensemble of decision trees during the training phase, utilizing random subsets of the input features to determine the optimal splitting nodes. The final classification output is determined by aggregating the predictions of all the individual trees, resulting in a highly robust model that is resistant to overfitting and capable of handling noisy or missing data. Support Vector Machines, conversely, function by identifying the optimal hyperplane in a multidimensional feature space that maximizes the margin of separation between different surface classes. When integrated with time-series data, these machine learning algorithms can be trained to recognize the specific temporal signatures of various change events, significantly improving classification accuracy [9]. More recently, the remote sensing community has rapidly adopted deep learning architectures, specifically Convolutional Neural Networks and Recurrent Neural Networks. Convolutional Neural Networks are explicitly designed to process grid-like spatial data, utilizing hierarchical layers of convolutional filters to automatically extract complex spatial features, such as edges, textures, and object shapes, directly from the raw imagery. This eliminates the need for manual feature engineering and dramatically improves performance in tasks such as urban building footprint extraction, road network mapping, and the detection of localized surface deformations. Recurrent Neural Networks, particularly Long Short-Term Memory networks, are uniquely suited for analyzing sequential data and are increasingly being deployed to model the temporal dependencies within satellite image time series, providing state-of-the-art results for dynamic surface process forecasting and continuous land cover monitoring.

4. Results and Discussion of Surface Process Dynamics

The application of the aforementioned analytical frameworks to various environmental domains yields detailed, quantitative results concerning the state of Earth surface processes. Analyzing these results provides critical insights into the mechanisms driving global change and highlights both the capabilities and the existing limitations of remote sensing technologies.

4.1 Urbanization and Land Cover Transformation

One of the most profound anthropogenic alterations to the Earth surface is rapid urbanization. Remote-sensing-driven analysis has been instrumental in quantifying the spatial extent, rate, and typological characteristics of urban expansion. By utilizing time-series analysis of medium and high-resolution optical data, researchers have documented the massive conversion of agricultural lands, forests, and wetlands into impervious surfaces across the globe. The results of these spatial analyses frequently reveal distinct patterns of urban morphology, differentiating between contiguous edge expansion, linear development along transportation corridors, and isolated leapfrog development in peri-urban zones. The accurate mapping of these sprawling patterns is essential for urban planners attempting to optimize infrastructure deployment and manage the environmental footprint of growing metropolitan regions. Furthermore, remote sensing methodologies are extensively utilized to study the localized climatic impacts of urbanization, most notably the urban heat island effect. Thermal infrared sensors mounted on satellite platforms can measure land surface temperature variations with high precision. Analytical results consistently demonstrate strong positive correlations between the density of artificial impervious surfaces and elevated land surface temperatures, while highlighting the cooling effects provided by urban green spaces and water bodies. Through the integration of optical land cover mapping and thermal data, researchers can model the specific thermal contributions of different urban materials and structural configurations. These insights are increasingly used to guide urban climate adaptation strategies, such as the strategic placement of urban forestry and the implementation of highly reflective roofing materials to mitigate extreme heat accumulation [10]. Beyond urban areas, broader land cover transformations driven

by agricultural expansion and intensification are thoroughly monitored using remote sensing. The conversion of natural biomes into managed agricultural landscapes represents a massive shift in global carbon and hydrological cycles. Multi-temporal satellite analysis allows for the accurate delineation of newly cleared agricultural land and the tracking of cropping intensity. In regions undergoing severe water stress, the continuous monitoring of agricultural extent, combined with satellite-derived estimates of actual evapotranspiration, provides critical data for the sustainable management of strained regional water resources and the enforcement of agricultural water quotas.

Table 2: Performance metrics of different change detection methodologies.

Methodology	Accuracy Range	Processing Speed	Main Advantage	Primary Limitation
Image Differencing	60% to 75%	Very Fast	Computational simplicity	High sensitivity to radiometric noise, subjective thresholding
Object-Based Analysis	80% to 92%	Moderate to Slow	Incorporates spatial context, reduces noise	Complex parameterization, computationally demanding segmentation
Time-Series Trajectory	85% to 95%	Slow	Captures temporal dynamics, dates specific events	Requires massive data archives, cloud computing resources necessary
Deep Learning (CNNs)	90% to 98%	Fast (Post-Training)	Highest accuracy for spatial feature extraction	Requires enormous labeled training datasets, "black box" interpretability

4.2 Ecological and Cryospheric Responses

In the natural environment, remote sensing frameworks provide indispensable results regarding ecological degradation and the impact of systemic climate change. The monitoring of global forest cover is perhaps the most prominent application. Time-series algorithms analyzing medium-resolution optical data have produced detailed global inventories of annual forest loss, disaggregating the causes into deforestation for commodity production, shifting agriculture, and natural disturbances like wildfires and pest outbreaks. The quantitative results derived from these systems are critical for enforcing international conservation agreements and supporting carbon credit verification mechanisms under global climate protocols. The analysis of these long-term datasets also reveals the varied recovery rates of different forest ecosystems, highlighting the resilience of certain biomes and the permanent state shifts occurring in others [11].

The cryosphere, encompassing the Earth ice sheets, glaciers, sea ice, and permafrost, is experiencing some of the most rapid and severe alterations due to anthropogenic global warming. Remote sensing is uniquely suited to monitor these remote and harsh environments. Multi-sensor fusion, combining optical imagery, synthetic aperture radar, and laser altimetry, provides a comprehensive suite of analytical tools to track cryospheric mass balance. Optical and radar data are routinely used to map the retreating margins of alpine glaciers and the diminishing extent of summer Arctic sea ice. Furthermore, spaceborne altimeters accurately measure the changing surface elevation of the Greenland and Antarctic ice sheets,

allowing researchers to calculate the enormous volumes of ice mass lost to the oceans.




Figure 3: Mechanism diagram of multi

Additionally, specialized interferometric synthetic aperture radar techniques have yielded vital results concerning the degradation of permafrost in high-latitude regions. As the permafrost thaws, the ground surface often subsides. By analyzing the phase shifts in repeated radar observations over seasonal and inter-annual timeframes, researchers can detect and map these millimeter-scale surface displacements. These findings provide critical early warning indicators of permafrost collapse, which poses severe risks to regional infrastructure and threatens to release massive stores of sequestered carbon and methane into the atmosphere, further exacerbating global warming trends [12]. Despite the profound success of remote-sensing-driven analysis, several challenges and limitations remain topics of intense discussion within the scientific community. The continuity of data archives is a persistent concern, as the failure of satellite instruments or the lack of subsequent funding for replacement missions can create unbridgeable gaps in critical time-series records. Furthermore, the integration of multi-sensor data, while scientifically highly valuable, introduces complex challenges regarding spatial scale mismatches, temporal harmonization, and the physical interpretation of fused variables. Additionally, the increasing reliance on complex deep learning algorithms necessitates the creation of vast, geographically diverse, high-quality ground truth datasets to properly train and validate the models. Without robust validation protocols, the automated outputs of these highly sophisticated algorithms risk propagating significant unseen errors into subsequent environmental policy and decision-making processes.

5. Conclusion

The comprehensive monitoring and analysis of Earth surface processes utilizing remote sensing technology constitute a fundamental pillar of contemporary environmental science. This paper has systematically detailed the conceptual foundations, technological advancements, and analytical methodologies that enable researchers to extract highly precise, actionable information from spaceborne observation platforms. The continuous evolution of satellite sensors, characterized by vast improvements in spatial precision, temporal frequency, and spectral depth, has fundamentally transformed our capacity to observe the intricate dynamics of the global environment. The transition from rudimentary, coarse-resolution snapshots to continuous, high-definition data streams represents a profound enhancement in our ability to quantify both slow, incremental environmental shifts and rapid, catastrophic disturbances.

The methodological framework surrounding remote sensing has simultaneously undergone a radical maturation. The implementation of rigorous preprocessing standards ensures the physical validity of the data, while the shift towards complex time-series analysis provides an unprecedented understanding of temporal trajectories and phenological cycles. Furthermore, the integration of advanced machine learning architectures, particularly deep learning networks, has significantly automated and refined the extraction of highly complex spatial features, pushing the boundaries of classification accuracy and predictive modeling. As demonstrated through the specific discussions on urban expansion, agricultural management, ecological degradation, and cryospheric retreat, these robust analytical paradigms provide the critical empirical data required to model global change and assess the far-reaching impacts of human activity on planetary systems. Moving forward, the field of remote-sensing-driven surface analysis will continue to be characterized by the integration of increasingly diverse datasets, leveraging the unique

synergies between optical, thermal, and active microwave instruments. The reliance on cloud-based computational infrastructures will only deepen, democratizing access to complex analytical tools and enabling real-time, global-scale environmental intelligence. However, to maximize the utility of these advancements, the scientific community must remain focused on developing transparent, highly interpretable algorithms and maintaining rigorous, extensive ground-validation networks. Ultimately, the continued refinement and application of remote sensing technologies are absolutely essential for informing sustainable governance, mitigating the impacts of severe environmental degradation, and securing a comprehensive understanding of the complex, ever-changing Earth system.

References

Zhang, C., & Zhao, Y. (2017). High precision deep sea geomagnetic data sampling and recovery with three-dimensional compressive sensing. IEICE TRANSACTIONS on Fundamentals of Electronics, Communications and Computer Sciences, 100(9), 1760-1762.

Lin, Y., Xue, B., Zhang, M., Schofield, S., & Green, R. (2025, November). YOLO and SGBM Integration for Autonomous Tree Branch Detection and Depth Estimation in Radiata Pine Pruning Applications. In 2025 40th International Conference on Image and Vision Computing New Zealand (IVCNZ) (pp. 1-6). IEEE.

Lin, Y., Xue, B., Zhang, M., Schofield, S., & Green, R. (2024, December). Deep Learning-Based Depth Map Generation and YOLO-Integrated Distance Estimation for Radiata Pine Branch Detection Using Drone Stereo Vision. In 2024 39th International Conference on Image and Vision Computing New Zealand (IVCNZ) (pp. 1-6). IEEE.

HAN, Z., ZHANG, L., ZHANG, B., ZOU, F., & SHANG, N. (2024). Progress on research and application of new non-destructive testing techniques in tomato quality inspection. Food Science, 45(1), 289-300.

Song, S., Tang, Y., & Qin, R. (2025). Synthetic Data Matters: Re-training with Geo-typical Synthetic Labels for Building Detection. IEEE Transactions on Geoscience and Remote Sensing.

Lijun, X., Yehui, Z., Yue, S., Fanglei, Z., Honghua, J., & Guangming, W. (2022). Research on the current situation of continuously variable transmission and electric drive technology. Journal of Chinese Agricultural Mechanization, 43(7), 81.

Zou, F., Hao, H., Yang, M., Tan, C., Chen, L., Wu, J., & Wang, H. (2025). Enhancing cyclodextrin glycosyltransferase-mediated potato starch modification via plasma-activated water and twin-screw extrusion treatment. Food Chemistry, 491, 145247.

Lin, Y., Xue, B., Zhang, M., Schofield, S., & Green, R. (2025, November). Performance Evaluation of Deep Learning for Tree Branch Segmentation in Autonomous Forestry Systems. In 2025 40th International Conference on Image and Vision Computing New Zealand (IVCNZ) (pp. 1-6). IEEE.

Wan, Y., Zhang, K., Xia, R., Li, Z., Zhang, Y., & Genovese, P. V. (2026). Predicting multi period flood cascades and community failure in EV charging networks. npj Natural Hazards, 3(1), 2.

Mulla, D. J. (2013). Twenty five years of remote sensing in precision agriculture: Key advances and remaining knowledge gaps. Biosystems Engineering, 114(4), 358–371.

Tang, Y., Zhang, G., Liu, J. K., & Qin, R. (2025). Weakly supervised land-cover classification of high-resolution images with low-resolution labels through optimized label refinement. International Journal of Remote Sensing, 46(5), 1913-1937.

Huete, A., Didan, K., Miura, T., Rodriguez, E. P., Gao, X., & Ferreira, L. G. (2002). Overview of the radiometric and biophysical performance of the MODIS vegetation indices. Remote Sensing of Environment, 83(1–2), 195–213.