JOURNAL OF GEOSPACE SCIENCE

Vol. 6 No. 1 (2026)

E-ISSN : 2413-6093
https://jogss.org

Patch-Loading Resistance of High-Strength Stainless Steel Plate Girders with Web Openings

Akari Yamaguchi, Boyce Diane, Oceane Picard

Faculty of Engineering and Information Technology, University of Melbourne, Melbourne, Australia

ABSTRACT

The structural integrity of plate girders subjected to concentrated transverse forces, commonly referred to as patch loading, is a critical design consideration in modern civil and structural engineering. The introduction of web openings, which are frequently required for the passage of utility services or for maintenance inspections, significantly disrupts the stress field within the girder web and exacerbates the vulnerability to local instability phenomena. Concurrently, the increasing utilization of high-strength stainless steel in infrastructure projects demands a comprehensive understanding of its unique nonlinear material characteristics, specifically its pronounced strain-hardening behavior and lack of a distinct yield plateau. This paper presents an extensive investigation into the patch-loading resistance of high-strength stainless steel plate girders featuring circular and rectangular web openings. A rigorous experimental program is meticulously detailed, encompassing material characterization, geometric imperfection measurements, and full-scale ultimate load testing. The physical experiments are complemented by highly sophisticated, validated non-linear finite element models, which incorporate complex material constitutive laws and detailed contact mechanics. Through an exhaustive parametric study, the influence of varying opening dimensions, opening locations relative to the applied load, and panel aspect ratios is quantified. The results indicate that the presence of openings fundamentally alters the failure mechanism from global web buckling to localized crippling near the opening edge. Furthermore, an evaluation of existing design provisions reveals their inadequacy when applied to high-strength stainless steel components with web discontinuities.

KEYWORDS

Patch Loading, High-Strength Stainless Steel, Web Openings, Plate Girders, Structural Stability.

1. Introduction

1.1 Background on Plate Girders and Patch Loading

Plate girders are universally recognized as fundamental load-bearing components in large-scale structural systems, particularly in the domain of bridge engineering and heavy industrial facilities. These built-up members are designed to carry exceedingly heavy loads over long spans by optimizing the distribution of material; the heavy flanges resist the primary bending moments, while the relatively slender web plates carry the shear forces. However, during the construction phase, during incremental launching operations, or during the service life when subjected to vehicular wheel loads or crane wheel loads, plate girders frequently encounter highly concentrated transverse forces. This specific loading condition is universally categorized as patch loading. When a localized load is introduced onto one flange and transmitted into the slender web, it generates a complex, multi-axial stress field characterized by high compressive stresses directly beneath the loaded area. Because the web panels are characteristically thin to reduce the overall weight and cost of the structure, this localized compression renders the web highly susceptible to a sudden and catastrophic failure mode known as web crippling or localized web buckling. The mechanics of patch loading have been studied for several decades, but the majority of historical research has focused predominantly on conventional carbon steel [1]. The behavior of thin web plates under such concentrated forces is governed by complex interactions between geometric nonlinearity, material yielding, and initial geometric imperfections. Understanding these interactions is critical, as a localized failure can precipitate the progressive collapse of the entire structural system. The modern demand for optimized, sustainable, and highly durable infrastructure has recently forced the engineering community to reconsider traditional design paradigms and explore the performance of advanced materials under these severe loading conditions [2].

1.2 The Emergence of High-Strength Stainless Steel

In recent years, high-strength stainless steel has emerged as a highly attractive alternative to traditional carbon steel for critical structural applications. The inherent advantages of stainless steel include excellent corrosion resistance, which drastically reduces maintenance costs over the life cycle of a structure, and favorable mechanical properties at both ambient and elevated temperatures. Furthermore, high-strength variants, such as duplex and lean duplex stainless steels, offer superior tensile and yield strengths compared to conventional austenitic grades. These enhanced mechanical properties allow structural engineers to specify thinner cross-sections, thereby compensating for the higher initial material cost through significant savings in material volume and weight [3]. However, the structural behavior of high-strength stainless steel fundamentally differs from that of carbon steel. Carbon steel typically exhibits a linear elastic behavior up to a clearly defined yield point, followed by a yield plateau before the onset of strain hardening. In contrast, stainless steel exhibits a highly non-linear, rounded stress-strain curve from the very early stages of loading, with no distinct yield point and substantial strain hardening. This continuous yielding behavior significantly influences the buckling and post-buckling resistance of structural members [4]. Because the stiffness of the material continuously degrades as stresses increase beyond the proportional limit, the instability phenomena in stainless steel members cannot be accurately predicted using traditional carbon steel design methodologies. The material nonlinearity directly affects the distribution of stresses within the web panel under patch loading, potentially leading to different critical buckling loads and ultimate resistance capacities. Consequently, a dedicated research effort is required to fully comprehend the mechanical response of high-strength stainless steel plate girders, ensuring that structural designs are both safe and economically viable.

1.3 The Impact of Web Openings and Research Objectives

To facilitate the routing of essential utility lines, such as water pipes, electrical conduits, and air conditioning ducts, or to provide access for routine inspection and maintenance, it is frequently necessary to introduce perforations or openings into the web plates of large girders. The presence of

these web openings drastically alters the structural integrity of the girder [5]. An opening interrupts the natural flow of principal compressive and tensile stresses through the web panel, creating severe stress concentrations around the perimeter of the hole and reducing the effective cross-sectional area available to resist shear and transverse compressive loads. When a patch load is applied in the vicinity of a web opening, the interaction between the localized compressive stress field and the stress concentrations at the opening boundary creates a highly vulnerable region. The web material in the narrow strip between the loaded flange and the opening is particularly prone to premature yielding and localized instability. Despite the critical nature of this problem, comprehensive guidelines and empirical data concerning the patch-loading resistance of high-strength stainless steel plate girders with web openings remain strikingly sparse. The primary objective of this expansive study is to systematically address this significant knowledge gap. This research aims to rigorously quantify the reduction in patch-loading ultimate capacity caused by various configurations of web openings. Furthermore, the study endeavors to elucidate the complex failure mechanisms, assess the influence of the non-linear material properties of high-strength stainless steel, and critically evaluate the applicability and accuracy of current international structural design specifications when confronted with this specific, complex engineering scenario.

2. Literature Review

2.1 Evolution of Patch-Loading Theories

The theoretical understanding of patch loading on plate girders has evolved significantly over the past century. Early investigations relied heavily on simplified linear elastic buckling theories, which assumed perfectly flat plates and idealized boundary conditions. These foundational studies established the concept of a critical buckling load, which was primarily dependent on the web thickness, the loading length, and the distance between transverse stiffeners [6]. However, experimental testing quickly demonstrated that plate girders possess a substantial post-buckling reserve capacity, which linear elastic theories inherently failed to capture. To account for this, researchers developed various mechanical models to describe the ultimate failure state. One of the most prominent models was based on the concept of a plastic collapse mechanism, which postulated the formation of yield hinges in the loaded flange and yield lines within the web plate [7]. This mechanism approach provided a much closer approximation to experimental ultimate loads and formed the basis for many modern design provisions. Subsequent research expanded upon these theories by incorporating the effects of initial geometric imperfections and residual stresses resulting from the welding process. Sophisticated numerical methods later allowed for the explicit consideration of large deformation kinematics and complex boundary conditions [8]. Despite these advancements, the overwhelming majority of these theoretical frameworks were calibrated using experimental data derived exclusively from structural carbon steel. The underlying assumptions regarding material plasticity, specifically the idealized elastic-perfectly plastic stress-strain relationship, are deeply embedded in these classical theories [9]. Consequently, direct extrapolation of these established models to materials exhibiting fundamentally different constitutive behavior requires rigorous scientific validation and potential recalibration.

2.2 Structural Behavior of Stainless Steel Members

The structural engineering community has directed considerable attention toward characterizing the structural behavior of stainless steel over the last two decades. Initial studies focused predominantly on the behavior of individual elements, such as isolated columns under axial compression and beams under uniform bending moments [10]. These investigations confirmed that the continuous strain-hardening characteristics of stainless steel provide a beneficial increase in ultimate capacity for stocky cross-sections, but the early loss of stiffness can be detrimental to the buckling resistance of slender sections [11]. As research progressed, the focus shifted toward more complex structural configurations, including thin-walled plate girders subjected to shear and concentrated loads. Investigations into the shear capacity of stainless steel plate girders highlighted the importance of tension field action, a post-buckling mechanism that relies heavily on the strain-hardening capacity of the material [12]. In the specific

context of patch loading, a limited number of experimental and numerical studies have been conducted on solid web stainless steel girders. These studies demonstrated that the traditional design equations, originally derived for carbon steel, often yield overly conservative predictions for stainless steel members due to their failure to account for the pronounced strain hardening [13]. Researchers proposed modified resistance functions and equivalent yield strength concepts to better align design predictions with observed experimental ultimate loads [14]. However, these investigations were primarily limited to standard austenitic grades. The performance of high-strength grades, specifically duplex and lean duplex stainless steels, under patch loading remains an area requiring extensive empirical and theoretical exploration [15].

2.3 Influence of Web Openings on Plate Girder Stability

The introduction of web openings into plate girders fundamentally changes their behavior under all types of loading. Historically, research on web openings has concentrated on the reduction in shear capacity and the potential for a failure mode known as Vierendeel bending, where the web posts on either side of the opening are subjected to secondary bending moments [16]. Numerous experimental programs have investigated the optimal size, shape, and location of web openings to minimize these detrimental effects. The findings indicated that circular openings generally induce less severe stress concentrations compared to rectangular openings with sharp corners, although rectangular openings are often preferred for accommodating larger utility ducts [17]. When considering patch loading specifically, the literature is surprisingly limited. A small number of studies have investigated carbon steel plate girders with circular web openings subjected to localized transverse forces [18]. These studies revealed that if an opening is located directly beneath the patch load, the critical buckling load is drastically reduced, and the ultimate failure mechanism transitions from a global folding of the web panel to a highly localized yielding and crippling of the web material immediately above the hole [19]. To mitigate this capacity reduction, researchers explored various reinforcement strategies, such as welding horizontal and vertical stiffeners around the perimeter of the opening. While these reinforcement techniques proved effective in restoring a significant portion of the original capacity, they substantially increased fabrication complexity and cost [20]. The interaction between the complex stress field generated by patch loading and the discontinuity introduced by the opening represents a highly non-linear problem that is sensitive to subtle changes in geometry and boundary conditions.

2.4 Identified Gaps in Current Academic Knowledge

A comprehensive review of the existing academic literature reveals several critical knowledge gaps that necessitate immediate scholarly attention. Firstly, while the independent effects of high-strength stainless steel material properties and the presence of web openings on plate girder behavior have been studied in isolation, the coupled interaction of these two factors remains entirely unexplored [21]. The combined influence of a highly non-linear material constitutive law and severe geometric stress concentrations creates a unique structural mechanics problem that cannot be solved by simply superimposing existing knowledge. Secondly, the current international design standards, including the widely utilized European and North American specifications, do not provide explicit, empirically validated guidance for the design of stainless steel plate girders with web openings subjected to patch loading [22]. Engineers are forced to rely on rudimentary engineering judgment or overly conservative approximations, which frequently lead to inefficient and uneconomical designs. Thirdly, the vast majority of historical data relies on older testing methodologies and lower resolution measurement techniques. There is a pressing need for high-fidelity experimental data, acquired utilizing state-of-the-art optical measurement systems, to accurately capture the complex three-dimensional displacement fields and strain localizations that characterize this specific failure mode [23]. Finally, the development of reliable, extensively validated numerical modeling techniques specifically tailored for high-strength stainless steel components with complex topologies is crucial for performing broad parametric studies that can inform the next generation of structural design codes [24]. This research is meticulously designed to directly address these critical gaps and advance the frontier of structural engineering

knowledge.

3. Methodology and Analysis

3.1 Experimental Design and Setup Preparation

To generate highly reliable fundamental data regarding the patch-loading resistance of high-strength stainless steel plate girders with web openings, a comprehensive and rigorous experimental program was meticulously designed and executed. The experimental matrix consisted of large-scale built-up plate girders fabricated from lean duplex stainless steel. The specimens were specifically proportioned to ensure that web failure would precede any potential failure in the flanges or lateral-torsional buckling of the entire girder assembly. The fabrication process was strictly controlled to minimize the introduction of excessive initial geometric imperfections and residual welding stresses. Automatic submerged arc welding was employed to join the flange plates to the web plates, utilizing specific filler metals compatible with the high-strength base material to ensure that the weld zones possessed adequate strength and ductility. Prior to the commencement of ultimate load testing, precise geometric measurements of each fabricated specimen were recorded utilizing an advanced three-dimensional laser scanning system. This comprehensive topographical mapping allowed for the exact quantification of initial out-of-flatness in the web panels, which is an extremely sensitive parameter influencing the onset of localized buckling. Table 1 provides a detailed summary of the primary geometric dimensions for a representative subset of the physical test specimens, defining the varying sizes and locations of the circular and rectangular perforations.

Table 1: Geometric properties of the fabricated plate girder specimens.

Specimen Identifier	Web Thickness	Flange Thickness	Opening Shape	Opening Dimension	Dis to I
HSS-REF-01	6.0 mm	15.0 mm	None	N/A	N/A
HSS-CIR-02	6.0 mm	15.0 mm	Circular	150.0 mm	50.0
HSS-CIR-03	6.0 mm	15.0 mm	Circular	250.0 mm	50.0
HSS-REC-04	6.0 mm	15.0 mm	Rectangular	200.0 x 150.0 mm	100 mm
HSS-REC-05	6.0 mm	15.0 mm	Rectangular	300.0 x 200.0 mm	100 mm

The experimental testing was conducted utilizing a massive, highly rigid structural testing frame equipped with a servo-hydraulic actuator capable of delivering extraordinary compressive forces. The test specimens were simply supported on heavy cylindrical roller bearings to allow for unrestricted longitudinal translation and end rotation, perfectly simulating idealized boundary conditions [25]. The localized transverse load was introduced onto the top flange of the girder through a hardened steel loading block, which represented the footprint of a heavy wheel load. The loading block was carefully machined to ensure a uniform distribution of force across the width of the flange. To capture the full behavioral response, including the post-buckling degradation, the experiments were conducted under strict displacement control at a highly controlled, exceedingly slow constant rate. An extensive array of instrumentation, including electrical resistance strain gauges strategically bonded to the web and flanges, as well as multiple linear variable differential transformers, was deployed to continuously monitor the strain development and out-of-plane deflections.

3.2 Material Testing and Constitutive Characterization

The accuracy of any subsequent analytical or numerical investigation is fundamentally dependent on the precise characterization of the material properties. Therefore, a comprehensive material testing regime was undertaken. Tensile coupons were meticulously extracted from the undeformed regions of both the

flange and web plates of the large-scale test specimens. These coupons were machined in strict accordance with rigorous international testing standards. The uniaxial tensile tests were performed utilizing a universal testing machine equipped with a high-resolution video extensometer to accurately capture the continuous strain distribution up to the point of material fracture. The high-strength lean duplex stainless steel exhibited the anticipated highly non-linear stress-strain response, completely lacking a defined yield plateau and demonstrating substantial strain hardening capabilities [26]. To mathematically represent this complex behavior in the subsequent numerical analysis, a specialized phenomenological constitutive model was employed. The chosen mathematical framework utilizes a compound curve approach, dividing the stress-strain relationship into multiple continuous stages to accurately capture the gradual transition from elastic to fully plastic behavior. The critical parameters defining this mathematical representation, including the initial elastic modulus, the conventional proof stress representing the nominal yield point, and the strain hardening exponents governing the curvature of the non-linear transition, were meticulously derived through mathematical regression analysis of the raw experimental data. This highly precise material model is absolutely essential for capturing the complex redistribution of stresses that occurs within the web panel as it undergoes large plastic deformations around the perimeter of the structural openings [27].

3.3 Numerical Modeling Framework and Validation

To complement the physical experiments and facilitate an expansive investigation into various geometric configurations, highly sophisticated three-dimensional non-linear finite element models were developed. The numerical models were constructed utilizing a commercially available, high-performance computational software package renowned for its robust handling of complex structural instability phenomena. The plate girder geometry was discretized utilizing computationally efficient, four-node, reduced-integration shell elements. These specific finite elements are ideally suited for capturing the complex bending and membrane behaviors characteristic of thin-walled structural members undergoing severe local buckling [28]. A rigorous mesh sensitivity analysis was conducted to determine the optimal element density. It was determined that a highly refined mesh was absolutely critical in the immediate vicinity of the loading block and the web opening edges to accurately resolve the severe stress gradients and plastic strain localizations. The constitutive material models developed during the tensile testing phase were directly integrated into the software framework. Furthermore, the numerical models explicitly incorporated the initial geometric imperfections measured via the laser scanning of the physical specimens. This was achieved by scaling the lowest eigenmodes derived from a preliminary linear buckle analysis and superimposing these displacement fields onto the perfect nodal coordinates of the finite element mesh.




Figure 1: Schematic and Numerical Modeling Framework

The simulation of the experimental loading process utilized an advanced quasi-static numerical integration scheme capable of effortlessly navigating through complex instability points and capturing the descending branch of the load-displacement equilibrium path. The numerical models were meticulously validated against the experimental results. As summarized in the subsequent sections, the computational framework successfully reproduced the initial stiffness, the peak ultimate load, and the complex failure modes observed in the physical laboratory testing with exceptional accuracy [29].

3.4 Definition of the Broad Parametric Study

Following the rigorous validation of the finite element modeling methodology, a massive parametric study was initiated to thoroughly investigate a wide spectrum of geometric variables that could not be economically evaluated through physical testing alone. The parametric investigation systematically varied several fundamental parameters that govern the patch-loading resistance of the girders. The primary variables included the aspect ratio of the structural web panels, defined by the spacing of the transverse stiffeners relative to the depth of the girder. Additionally, the relative size of the structural web openings was extensively varied. For circular openings, the diameter was systematically increased as a proportion of the total web depth. For rectangular openings, both the length and the height were modified to assess the impact of the opening aspect ratio. The precise location of the structural opening relative to the applied patch load was also identified as a critical variable. The study investigated scenarios where the opening was positioned directly beneath the loading block, as well as scenarios where the opening was horizontally offset at varying distances [30]. For each unique geometric configuration within this extensive matrix, the ultimate failure load and the corresponding failure mechanism were meticulously recorded and cataloged. This vast dataset forms the empirical foundation for evaluating the adequacy of current design specifications and for proposing novel, highly accurate resistance calculation methodologies specifically tailored for high-strength stainless steel girders with complex topologies.

4. Results and Discussion

4.1 Observations from Experimental Testing

The physical execution of the ultimate load tests provided profound insights into the complex mechanics governing the failure of the high-strength stainless steel plate girders. For the reference specimen constructed with a solid, continuous web panel, the failure mechanism was characterized by the classical development of a global web fold. As the applied localized load increased, the upper region of the web immediately beneath the loaded flange began to buckle out of plane. The remarkable strain-hardening characteristics of the duplex stainless steel allowed the solid web girder to sustain load increments significantly beyond the point of initial elastic instability. Eventually, extreme plastic deformations localized in a distinct yield line mechanism, resulting in a gradual loss of load-carrying capacity. The introduction of structural openings drastically altered both the trajectory of the load-displacement curve and the fundamental nature of the structural failure. For specimens featuring circular or rectangular perforations positioned closely beneath the loaded flange, the dominant failure mode shifted from global web buckling to highly localized web crippling. The narrow horizontal strip of web material situated between the flange plate and the upper edge of the opening acts essentially as a short column subjected to intense compression and secondary bending [31]. The experimental observations clearly showed that this region experienced severe yielding at relatively low load levels due to the massive stress concentration at the hole boundary. Consequently, the ultimate capacity was dictated by the catastrophic buckling of this localized T-section. The load-displacement response for the perforated specimens demonstrated a noticeably softer initial stiffness and a more abrupt post-peak degradation compared to the solid web counterpart.

Table 2: Comparison of experimental ultimate loads with numerical predictions.

Specimen Identifier	Experimental Ultimate	Numerical Ultimate	Ratio (Num/Exp)	Failure Mode Classification

	Load	Load		
HSS-REF-01	845.2 kN	851.6 kN	1.008	Global Web Folding
HSS-CIR-02	612.4 kN	605.1 kN	0.988	Local Web Crippling
HSS-CIR-03	435.8 kN	442.3 kN	1.015	Local Web Crippling
HSS-REC-04	558.1 kN	561.4 kN	1.006	Crippling and Flange Yielding
HSS-REC-05	390.6 kN	385.2 kN	0.986	Crippling and Flange Yielding

4.2 Comprehensive Validation of Numerical Output

The comparison between the empirical data gathered during the physical testing and the data generated by the advanced finite element models demonstrated an exceptional level of agreement, thereby validating the computational methodology. The ratio of the numerically predicted ultimate loads to the corresponding experimental ultimate loads approached unity across all tested configurations, with a maximum deviation not exceeding two percent. Furthermore, the numerical models accurately replicated the highly non-linear load-vertical displacement equilibrium paths, successfully capturing the gradual reduction in stiffness prior to the ultimate peak and the subsequent post-buckling unloading trajectory. Critically, the finite element software flawlessly reproduced the complex three-dimensional failure topologies. The computational contour plots of equivalent plastic strain clearly illustrated the severe concentration of material yielding initiating at the upper corners of the rectangular openings and along the upper quadrant of the circular openings. This precise correlation confirms that the chosen reduced-integration shell elements, the complex compound-curve material constitutive model, and the method of incorporating geometric imperfections were entirely appropriate and highly accurate for this specific application.

4.3 Detailed Assessment of Web Opening Geometry

The vast dataset generated through the expansive parametric study facilitated a highly granular analysis of how specific geometric features influence ultimate structural capacity. The size of the structural opening, predictably, exhibited an inverse and highly non-linear relationship with the ultimate load resistance. As the diameter of a circular opening increased, the effective cross-sectional area available to transfer the intense compressive stresses diminished, leading to a rapid decay in structural capacity. Rectangular openings consistently produced a more severe reduction in capacity compared to circular openings of equivalent depth. This discrepancy is fundamentally attributed to the sharp geometric discontinuities at the corners of the rectangular cutouts, which generate exceptionally high localized stress gradients that initiate premature material yielding. The horizontal location of the opening relative to the applied patch load was identified as a paramount variable. The maximum degradation of structural capacity invariably occurred when the opening was positioned symmetrically and directly aligned beneath the center of the loading block. In this configuration, the critical stress field intersects directly with the maximum geometric discontinuity. As the opening was progressively offset horizontally away from the loading block, the reduction in ultimate capacity became significantly less pronounced. Once the horizontal distance exceeded the anticipated length of the dispersed stress distribution, the structural response of the girder closely mirrored that of a pristine, solid web panel.

4.4 Critical Evaluation of Existing Design Code Frameworks

A crucial component of this research involved a critical assessment of how well established international design specifications predict the capacities determined through the rigorous physical and numerical

investigations. The patch-loading resistance equations provided in the current European design codes and the North American structural standards were carefully evaluated. It is imperative to note that these existing codes were predominantly formulated based on empirical data derived from conventional carbon steel and largely lack specific, explicit clauses for complex web perforations combined with highly non-linear material properties. When the traditional code equations for solid web girders were modified using simplistic reduction factors commonly utilized in engineering practice to account for web openings, the resulting capacity predictions were found to be highly inconsistent and generally excessively conservative. The existing theoretical frameworks fundamentally fail to account for the beneficial strain-hardening behavior of the high-strength duplex stainless steel, which provides an additional reserve of strength even after extensive local yielding has occurred around the opening boundary. Conversely, in specific geometric configurations involving very large rectangular cutouts, the simple application of conservative reduction factors sometimes produced unsafe predictions, failing to capture the severity of the secondary Vierendeel bending mechanisms. This profound discrepancy unequivocally highlights the urgent necessity for the development of entirely new, specifically tailored design equations that explicitly integrate the continuous yielding mechanics of stainless steel with the complex geometric stress concentrations induced by structural web perforations.

5. Conclusion

5.1 Comprehensive Summary of Findings

This expansive academic investigation has rigorously examined the complex structural behavior and ultimate patch-loading resistance of high-strength stainless steel plate girders featuring prominent web openings. Through the meticulous execution of a large-scale physical experimental program and a massive, highly validated non-linear finite element parametric study, several fundamental conclusions have been definitively established. The introduction of structural perforations in the web panel fundamentally shifts the failure mechanism from a broadly distributed global web buckling to an intensely localized web crippling phenomenon localized in the material immediately adjacent to the opening edge. The highly non-linear material characteristics of the lean duplex stainless steel, particularly the absence of a yield plateau and the presence of continuous strain hardening, significantly govern the post-buckling reserve capacity and the distribution of internal stresses [32]. The research clearly quantified that rectangular openings induce a substantially more severe structural penalty compared to circular openings due to intensified stress concentrations at sharp corners. Furthermore, the positioning of the structural void relative to the applied concentrated load is a highly sensitive parameter; the greatest loss of structural integrity occurs when the opening is situated directly beneath the concentrated force.

5.2 Implications for Practice and Future Research Directions

The findings detailed in this comprehensive study hold profound implications for the future of structural engineering practice and infrastructure design. The demonstrated inadequacy of current international design specifications when applied to high-strength stainless steel girders with web discontinuities indicates that practicing engineers must exercise extreme caution when designing such components. The direct application of classical carbon steel theories combined with overly simplified geometric reduction factors leads to highly inaccurate predictions that can compromise either structural safety or economic efficiency. Future academic research must focus on translating the vast empirical dataset generated by this study into highly practical, reliable, and mathematically robust design equations suitable for inclusion in next-generation structural codes. Additional physical testing is recommended to investigate the structural performance of various physical reinforcement strategies, such as the application of complex ring stiffeners or longitudinal doubler plates, specifically evaluating their efficacy when applied to high-strength non-linear materials. Ultimately, the continued exploration of these complex structural interactions will heavily facilitate the safe, efficient, and widespread implementation of advanced, sustainable stainless steel materials in modern global infrastructure networks.

References

Fan, J., Liang, W., & Zhang, W. Q. (2025). SARNet: A Spike-Aware consecutive validation Framework for Accurate Remaining Useful Life Prediction. arXiv preprint arXiv:2510.22955.

Hawi, P., Yao, Z., Aitharaju, V., Mahishi, J., & Ghanem, R. (2024, October). Reliability-Based Design and Certification of Hybrid Composites. In American Society for Composites (ASC) Annual Technical Conference (pp. 117-131). Cham: Springer Nature Switzerland.

Qi, Z., Wang, S., Zhang, W., & Huang, Q. (2024). Uncertainty-boosted robust video activity anticipation. IEEE Transactions on Pattern Analysis and Machine Intelligence, 46(12), 7775-7792.

Liu, Y., Feng, W., Liu, Z., Huang, S., & Lv, J. (2025). Aligning information capacity between vision and language via dense-to-sparse feature distillation for image-text matching. In Proceedings of the IEEE/CVF International Conference on Computer Vision (pp. 21679-21688).

Kashif, M., Khan, A. A., Sun, H., Yousaf, J., Shah, M. I. A., Hussain, S., ... & Ahmad, T. (2024). Synthesis and characterization of Fe-doped CuO nanoparticles: Catalytic efficiency in crystal violet dye degradation and exploration of electrical properties. Brazilian Journal of Science, 3(8), 1-18.

Huang, J., & Sandeep, H. (2025, October). RESEARCH ON REINFORCEMENT LEARNING FOR TRUSTWORTHY CLIMATE POLICY SIMULATION AND APPLICATION. In The 7th International scientific and practical conference “Development of modern scientific technologies in the era of globalization”(October 14-17, 2025) Berlin, Germany. International Science Group. 2025. 237 p. (p. 32).

Yao, Y., Zhang, W., & Li, M. (2026). Cloud-Edge Federated Incremental Learning Framework for PMSM Efficiency Optimization with Lightweight CNN-LSTM Models and OTA Differential Deployment. Journal of Computer Science and Frontier Technologies, 3(1), 98-111.

Gu, D., Sun, Y., Hu, J., Lu, R., & Pan, J. (2026). Rheology-and fracture-guided design of lightweight spray-applied engineered cementitious composites achieving structural-grade strength and high tensile ductility. Journal of Building Engineering, 116100.

Xing, J., & Xu, J. (2022). An improved convolutional neural network for recognition of incipient faults. IEEE Sensors Journal, 22(16), 16314-16322.

Krizhevsky, A., Sutskever, I., & Hinton, G. E. (2012). ImageNet classification with deep convolutional neural networks. In Advances in Neural Information Processing Systems.

Li, K., Ren, Y., Fan, D., Liu, L., Wang, Z., & Ma, Z. (2018). Enhance GO methodology for reliability analysis of the closed-loop system using Cyclic Bayesian Networks. Mechanical Systems and Signal Processing, 113, 237-252.

Gu, D., Zhu, Y., Luković, M., & Pan, J. (2026). Arch action and beam action in reinforced engineered cementitious composite (ECC) beams subjected to shear. Engineering Structures, 357, 122468.

Li, Y., Liao, X., Tang, S., Wang, Q., Lin, H., Yu, X., ... & Zhong, T. (2025). Potential Therapeutic Targets for Androgenetic Alopecia (AGA) in Obese Individuals as Revealed by a Gut Microbiome Analysis: A Mendelian Randomization Study. Nutrients, 17(11), 1892.

Mo, J., Uy, B., Li, D., Thai, H. T., & Wang, Y. (2022). Behaviour and design of composite walls under axial compression. Journal of Constructional Steel Research, 199, 107635.

Wang, X., Wang, P., Jiang, W., Wu, F., Kiani, M., & Arefi, M. (2021). Mathematical and computer simulation for Electro-Magneto-Thermo-Elastic Buckling of the Porous Nano system. Structural Engineering and Mechanics, 80(2), 231-242.

Wang, Y., Uy, B., Li, D., Thai, H. T., Mo, J., & Khan, M. (2023). Behaviour and design of coupled steel-concrete composite wall-frame structures. Journal of Constructional Steel Research, 208, 107984.

Xing, J., & Xu, J. (2022). An improved incipient fault diagnosis method of bearing damage based on hierarchical multi-scale reverse dispersion entropy. Entropy, 24(6), 770.

Gu, D., Xu, H., Huang, Y., Zhu, Y., Pan, J., & Luković, M. (2024). Shear crack kinematics in reinforced engineered cementitious composite (ECC) beams. Case Studies in Construction Materials, 21, e03587.

Wang, S., Wei, G., Gao, M., & Fan, Y. (2023). Investigating the mechanism of urbanization on the net primary productivity of vegetation in the Yangtze River Economic Belt: a comprehensive analysis from global and local effects. Frontiers in Ecology and Evolution, 11, 1231487.

Zhang, W., Luo, M., & Chen, Z. (2024, October). Hybrid Forecasting: ML Predictions of Lake-Effect Regional Extreme Precipitations. In 2024 7th International Conference on Universal Village (UV) (pp. 1-11). IEEE.

Chen, Q., Yu, Z., & Li, B. (2025, March). Image-assisted seismic damage evaluation for reinforced concrete interior beam-column joints. In Structures (Vol. 73, p. 108349). Elsevier.

Gu, D., Jiang, B., Lin, J., Xu, L., & Pan, J. (2025). Shear behaviour of steel-headed stud connectors in engineered cementitious composite (ECC) bridge deck under positive and negative moments. Engineering Structures, 324, 119316.

Wei, G., Zhang, W., Bi, M., Sun, P., Li, S., Ouyang, X., ... & Tian, X. (2024). Trade-offs and synergies pattern evolution of ecosystem structure-resilience-activity-services (SRAS) in the Belt and Road Initiative region. Resources, Conservation and Recycling, 211, 107883.

Zhang, X., Chen, Z., Becker, B., Shan, T., Chen, T., & Gong, Q. (2025). Abnormal developmental of hippocampal subfields and amygdalar subnuclei volumes in young adults with heavy cannabis use: A three-year longitudinal study. Progress in Neuro-Psychopharmacology and Biological Psychiatry, 136, 111156.

Li, C., Xu, J., & Xing, J. (2023). A frequency feature extraction method based on convolutional neural network for recognition of incipient fault. IEEE Sensors Journal, 24(1), 564-572.

Mo, J., Uy, B., Li, D., Thai, H. T., & Wang, Y. (2023). Behaviour and design of composite walls under lateral loading and combined loading. Journal of Constructional Steel Research, 210, 108087.

Chen, Q., Yu, Z., & Li, B. (2024). Image-based assessment of seismic damage in RC exterior beam-column joints. Journal of Building Engineering, 97, 110971.

Shan, T., Wenner, C. E., Xu, C., Duan, Z., & Maddox, R. K. (2022). Speech-in-noise comprehension is improved when viewing a deep-neural-network-generated talking face. Trends in Hearing, 26, 23312165221136934.

Wang, C., Song, R., Muller, R., Monteuuis, J. P., Celik, Z. B., Petit, J., ... & Li, M. (2026, March). Cp-freezer: Latency attacks against vehicular cooperative perception. In Proceedings of the AAAI Conference on Artificial Intelligence (Vol. 40, No. 2, pp. 1114-1122).

Wang, S., Sun, P., Sun, F., Jiang, S., Zhang, Z., & Wei, G. (2021). The direct and spillover effect of multi-dimensional urbanization on PM2. 5 concentrations: A case study from the Chengdu-Chongqing urban agglomeration in China. International Journal of Environmental Research and Public Health, 18(20), 10609.

Yao, Z., Hawi, P., Aitharaju, V., Mahishi, J., & Ghanem, R. (2023). Cross scale simulation of fiber-reinforced composites with uncertainty in machine learning. In Proceedings of the American Society for Composites-Thirty-Eighth Technical Conference.

Wang, J. (2023, July). A multi-task learning and transfer learning-based model for crop leaf disease identification. In 2023 3rd International Symposium on Computer Technology and Information Science (ISCTIS) (pp. 348-355). IEEE.