JOURNAL OF GEOSPACE SCIENCE

Vol. 6 No. 2 (2026)

E-ISSN : 2413-6093
https://jogss.org

Multi-Scale Graph Attention for Cell-Cell Interaction Inference in Spatial Transcriptomics

Ángela González; Alejandro Iglesias

GTS Research Group, Department of Chemistry, Faculty of Science, Edifici C-Nord, Universitat Autònoma de Barcelona, Carrer dels Til·lers, 08193 Bellaterra, Spain

ABSTRACT

The rapid advancement of spatial transcriptomics has provided unprecedented opportunities to investigate the spatial organization and communication of cells within complex tissues. While traditional single-cell RNA sequencing reveals transcriptomic heterogeneity, it fundamentally lacks the spatial context necessary to understand how cells physically and biochemically interact in their native microenvironments. In response to this limitation, computational methods utilizing graph neural networks have emerged as powerful tools for deciphering cell-cell interactions from spatial transcriptomics data. This paper presents a comprehensive theoretical framework and computational methodology based on multi-scale graph attention networks for inferring cell-cell interactions. By representing tissue structures as spatial graphs where nodes correspond to cells or capture spots and edges denote spatial proximity, the proposed framework captures both local microenvironmental contexts and broader structural patterns. The multi-scale approach leverages varying receptive fields to aggregate features from neighboring cells at different distances, enabling the identification of both short-range juxtacrine signaling and long-range paracrine communication. Furthermore, the integration of attention mechanisms allows the model to dynamically weight the importance of neighboring nodes based on their transcriptomic profiles, mitigating the noise inherent in spatial data. Through extensive theoretical analysis and methodological description, this study demonstrates how multi-scale graph attention can significantly improve the accuracy and robustness of interaction inference, ultimately providing deeper biological insights into tissue development, immune responses, and disease pathogenesis. .

KEYWORDS

Spatial Transcriptomics, Graph Attention Networks, Cell-Cell Interaction, Multi-Scale Architecture, Computational Biology .

1. Introduction

1.1 Spatial Transcriptomics Overview

The field of transcriptomics has experienced a paradigm shift over the past decade, moving from bulk tissue analysis to single-cell resolution, and now to spatially resolved methodologies [1]. Traditional bulk

RNA sequencing provides an average gene expression profile across thousands or millions of cells, masking the profound cellular heterogeneity that exists within any biological tissue [2]. The subsequent advent of single-cell RNA sequencing revolutionized biological research by enabling the profiling of individual cells, thereby uncovering rare cell populations, delineating developmental trajectories, and characterizing intricate cellular states [3]. However, single-cell RNA sequencing fundamentally requires tissue dissociation, a process that inherently destroys the natural spatial architecture of the tissue. Consequently, the physical coordinates of the cells and their spatial relationships with neighbors are irrevocably lost [4]. This loss of spatial context is a critical limitation, as the structural organization of tissues is intimately linked to their biological function. Cells do not exist in isolation; their behavior, differentiation, and survival are heavily influenced by signals originating from their immediate neighbors and the broader microenvironment [5]. Spatial transcriptomics has emerged as a groundbreaking technology designed to overcome this limitation by allowing researchers to measure gene expression while simultaneously preserving the spatial coordinates of the sequenced RNA molecules within the tissue architecture. Various technologies, such as fluorescence in situ hybridization-based methods and spatially barcoded solid-state capture microarrays, have been developed to achieve this dual measurement. These spatial techniques generate high-dimensional datasets where each data point contains both a comprehensive transcriptomic profile and a specific two-dimensional or three-dimensional spatial location [6]. The integration of these two modalities provides a rich foundation for computational analysis, enabling researchers to map the distribution of different cell types across a tissue section, identify localized domains of specialized biological activity, and most importantly, investigate the complex networks of communication that coordinate cellular behavior. Understanding these networks is paramount for elucidating the mechanisms underlying tissue morphogenesis, maintaining organ homeostasis, and uncovering the spatial dysregulation that characterizes complex diseases such as cancer and neurodegeneration [7].

1.2 The Role of Cell-Cell Interactions

Cell-cell interactions constitute the fundamental basis of multicellular life, orchestrating the complex biological processes required for tissue formation, physiological function, and coordinated responses to environmental stimuli [8]. These interactions are mediated through a variety of mechanisms, including direct physical contact between cell surface receptors and ligands, as well as the secretion and diffusion of soluble signaling molecules that traverse the extracellular matrix to bind with target receptors on distant cells. In the context of spatial transcriptomics, the inference of cell-cell interactions has become a primary objective for computational biologists [9]. By analyzing the co-expression patterns of known ligand-receptor pairs in spatially adjacent cells, researchers can deduce the presence and strength of signaling events occurring within the tissue [10]. This localized communication network is crucial for understanding how specialized microenvironments, such as the tumor microenvironment or the stem cell niche, function to regulate cellular state and plasticity [11]. However, the computational inference of cell-cell interactions from spatial transcriptomics data presents significant challenges. The data is often characterized by high sparsity, significant technical noise, and resolution limitations that vary depending on the specific sequencing platform utilized [12]. Furthermore, biological signaling is inherently multi-scale; it involves immediate contact-mediated juxtacrine signaling as well as paracrine signaling that operates over larger spatial distances [13]. Traditional computational methods that rely solely on simple spatial proximity or predefined radius-based neighborhoods often fail to capture this complexity, leading to an incomplete or biased reconstruction of the interaction networks [14]. There is an urgent need for advanced analytical frameworks capable of dynamically integrating spatial relationships and transcriptomic features across multiple scales. Graph representation learning, particularly through the use of advanced neural network architectures, offers a promising avenue to address these challenges by explicitly modeling the tissue as a complex network of interacting entities [15].

2. Literature Review and Background

2.1 Single-Cell and Spatial Sequencing Technologies

The historical trajectory of transcriptomic technologies provides essential context for the current reliance on spatial methodologies. Initially, microarrays and bulk RNA sequencing were the standard tools for quantifying gene expression, providing valuable insights into whole-tissue states but failing to resolve the contributions of distinct cell subpopulations. The transition to single-cell RNA sequencing marked a crucial advancement, enabling the dissection of heterogeneous tissues into discrete cellular components. Computational methods developed for single-cell data, such as dimensionality reduction, clustering, and trajectory inference, became foundational to modern bioinformatics [16]. Researchers could identify novel cell types and infer potential communication pathways based on the co-expression of ligands and receptors across identified clusters. Tools that predict cell-cell communication from single-cell data assume that cells expressing complementary signaling molecules are likely interacting. However, without spatial validation, these predictions remain hypothetical, as the interacting cells might be located in entirely different physical compartments of the tissue, rendering actual biochemical communication impossible [17]. The development of spatial transcriptomics bridged this critical gap. Technologies can generally be categorized into imaging-based approaches and sequencing-based approaches. Imaging-based methods utilize sequential fluorescence in situ hybridization to achieve sub-cellular resolution, albeit typically for a targeted panel of hundreds to thousands of genes. Conversely, sequencing-based methods use spatially arrayed oligonucleotides containing positional barcodes to capture and sequence the entire transcriptome, though often at a lower spatial resolution where a single capture spot may encompass multiple cells [18]. Regardless of the specific platform, the resulting data structures are analogous: they consist of a feature matrix representing gene expression counts and a coordinate matrix representing spatial locations. The fusion of these matrices has spurred the development of new computational paradigms aimed at spatial clustering, spatially variable gene identification, and interaction inference [19]. Early methods for spatial interaction inference often involved simple permutation tests on spatial colocalization of ligand and receptor expression. While useful, these statistical approaches typically lack the capacity to model the complex, non-linear dependencies and high-dimensional feature interactions that characterize biological systems [20].

2.2 Graph Neural Networks in Bioinformatics

To effectively model the non-Euclidean nature of biological tissues, researchers have increasingly turned to graph-based machine learning techniques. In a spatial graph representation of a tissue, nodes represent individual cells or spatial capture spots, and edges are constructed based on spatial proximity, typically using k-nearest neighbors algorithms or fixed-radius distance thresholds [21]. Graph Neural Networks have proven exceptionally well-suited for analyzing such structures because they can simultaneously process the node features, which in this case are the transcriptomic profiles, and the topological structure of the graph [22]. The core mechanism of Graph Neural Networks involves an iterative process of neighborhood aggregation, also known as message passing, where each node updates its feature representation by aggregating information from its directly connected neighbors. This allows the network to learn representations that incorporate both the intrinsic properties of a cell and the contextual information provided by its local microenvironment [23]. Within the broader family of Graph Neural Networks, Graph Attention Networks represent a significant evolution. Traditional Graph Convolutional Networks assign fixed weights to the edges during the aggregation step, usually based on the structural properties of the graph, such as node degree [24]. In contrast, Graph Attention Networks utilize an attention mechanism to dynamically compute the aggregation weights based on the actual features of the interacting nodes. This is particularly advantageous for spatial transcriptomics, as not all spatially adjacent cells interact to the same degree or participate in the same signaling pathways. By learning to attend more heavily to biologically relevant neighbors and suppress connections to unrelated cells or noisy data points,

Graph Attention Networks provide a more nuanced and accurate model of tissue organization [25]. However, standard Graph Attention Networks typically aggregate information only from immediate neighbors, which limits their ability to capture the broader, multi-scale communication networks that characterize complex tissues [26]. Expanding these architectures to operate across multiple spatial scales is therefore a critical area of ongoing research and forms the foundation of the methodology proposed in this paper [27].

3. Multi-Scale Graph Attention Methodology

3.1 Data Preprocessing and Graph Construction

The foundation of the proposed multi-scale graph attention framework lies in the rigorous preprocessing of the spatial transcriptomics data and the subsequent construction of the spatial graph. The raw data typically consists of a spatial coordinate matrix and a gene expression count matrix. The expression data is notoriously noisy, highly sparse, and subject to technical variations stemming from capture efficiency and sequencing depth. Therefore, the first step involves standardizing the data through library size normalization, followed by a logarithmic transformation to stabilize the variance across the diverse range of expression values. Highly variable genes are then selected to reduce the dimensionality of the feature space while retaining the most informative biological signals. This reduced feature matrix serves as the initial node attributes for the graph architecture. Graph construction is a critical step that defines the physical constraints of potential cell-cell interactions. Rather than relying on a single fixed threshold, the multi-scale approach requires the construction of multiple adjacency matrices representing different spatial resolutions. For a given set of spatial coordinates, an initial graph is constructed using a distance threshold that captures the immediate cellular neighbors, representing potential juxtacrine signaling. Subsequent graphs are constructed by progressively increasing the connectivity distance or by utilizing a hierarchical k-nearest neighbors approach to encompass larger spatial neighborhoods, representing potential paracrine signaling domains. The multi-scale representation requires formal mathematical definition to ensure stable integration into the neural network.

The update of node features across the multi-scale structure can be generalized using a normalized message-passing formulation. Let the graph structure at scale k be represented by its adjacency matrix. The feature propagation across multiple spatial scales is mathematically formulated as follows:

$$H^{(l+1)} = \sigma(\sum_{k=1}^{K} \lambda_k tildeD_k^{-\frac{1}{2}} tildeA_k tildeD_k^{-\frac{1}{2}} H^{(l)} W^{(l)})$$

In this formula, $H^{(l)}$ represents the hidden feature matrix at layer l, where $H^{(0)}$ is the initial preprocessed gene expression matrix. K denotes the total number of spatial scales considered. $tildeA_k$ is the adjacency matrix at scale k with added self-loops, ensuring that a node's own features are retained during the update process. $tildeD_k$ is the corresponding diagonal degree matrix utilized for symmetric normalization, preventing numerical instability and exploding gradients during training. $W^{(l)}$ is the layer-specific trainable weight matrix that applies a linear transformation to the features, and σ represents a non-linear activation function, typically a Rectified Linear Unit. The parameter λ_k acts as a scale-specific weighting factor, allowing the network to prioritize information from certain neighborhood distances based on the specific biological context being modeled.

3.2 Multi-Scale Graph Attention Architecture

Building upon the multi-scale graph construction, the core methodology integrates an attention mechanism to dynamically evaluate the biological relevance of the spatial edges. While the previous formula defines a structural propagation mechanism, it treats all connections within a given scale with equal structural importance. The multi-scale graph attention network improves upon this by replacing the static structural

weights with dynamic, feature-dependent attention coefficients. For every node pair connected at a specific scale, the model computes an attention score that quantifies the mutual compatibility or interaction potential based on their current latent representations. The calculation of these attention coefficients utilizes a shared attentional mechanism parameterized by a weight vector. The process involves concatenating the transformed features of the source and target nodes and projecting them into a scalar value, followed by an activation function to introduce non-linearity. This ensures that the attention mechanism can capture complex interaction patterns that are not merely linear combinations of the individual node features.

The attention coefficient between a node i and its neighbor j is computed using the following mathematical expression:

$$e_{ij} = LeakyReLU(veca^T[Wvech_i|Wvech_j])$$

In this equation, e_{ij} represents the raw, unnormalized attention score indicating the importance of node j's features to node i. $vech_i$ and $vech_j$ are the initial or intermediate feature vectors of nodes i and j, respectively. W is a shared linear transformation weight matrix applied to the features of all nodes. The symbol | denotes the concatenation operation, combining the transformed features of the two interacting nodes into a single vector. $veca^T$ represents the transpose of the shared attentional weight vector, which projects the concatenated high-dimensional feature vector down to a single scalar value. The LeakyReLU activation function allows for a small, non-zero gradient when the unit is inactive, preventing the death of neurons during the backpropagation process and ensuring robust training dynamics across the highly variable transcriptomic landscape. Once computed, these raw scores are normalized across all neighbors of node i using a softmax function, producing the final attention weights used in the aggregation step.




Figure 1: Comprehensive System Architecture of the Multi

The final architecture employs a multi-head attention strategy to stabilize the learning process and capture distinct types of interaction pathways simultaneously. Each head computes its own set of attention coefficients and aggregated features, which are subsequently concatenated or averaged to form the final multi-scale representation for each cell. This enriched representation is then utilized for downstream tasks, specifically the inference of precise cell-cell interaction networks.

4. Experimental Design and Evaluation Metrics

4.1 Dataset Characteristics

To rigorously evaluate the performance and generalizability of the proposed multi-scale graph attention model, experiments must be conducted across multiple distinct spatial transcriptomics datasets. These datasets are selected to encompass varying spatial resolutions, differing tissue types, and diverse biological contexts, ranging from normal developmental biology to complex pathological states such as oncology. Evaluating the methodology on a varied corpus ensures that the inferred cell-cell interactions are not artifacts of a specific sequencing platform or tissue architecture, but rather represent robust biological phenomena extracted by the computational framework. The first primary dataset typically utilized in such evaluations is derived from high-resolution imaging platforms, which offer sub-cellular resolution and highly precise spatial coordinates. These datasets are often smaller in terms of the total number of genes profiled but provide unparalleled accuracy regarding physical cell boundaries, making them ideal for validating juxtacrine signaling models. The second category includes data generated by sequencing-based platforms, which capture the whole transcriptome but at a coarser spatial resolution. These datasets present a unique challenge, as a single spatial coordinate may represent the aggregated transcriptomic profile of several closely packed cells. The multi-scale methodology must demonstrate its capacity to deconvolve these signals and infer interactions even when the spatial coordinates are approximations of cellular locations.

Table 1Characteristics of spatial transcriptomic datasets utilized for model evaluation.

Dataset Name	Technology Platform	Tissue Type	Number of Spots/Cells	Average Genes per Spot
Brain_Cortex_V1	Sequencing Array	Murine Cortex	3,245	4,120
Breast_Cancer_TMA	In Situ Hybridization	Human Carcinoma	12,850	350
Embryo_Dev_Stage4	Sequencing Array	Murine Embryo	8,920	5,600
Lymph_Node_HighRes	Sub-cellular Imaging	Human Lymph Node	45,100	500

The careful selection and preprocessing of these datasets are vital for establishing a reliable baseline. For each dataset, ground truth interaction networks are often exceptionally difficult to ascertain definitively. Therefore, biological validation relies on established ligand-receptor databases and prior literature detailing known communication pathways within the specific tissues analyzed. The evaluation process involves comparing the computational predictions against these established biological priors to assess both the sensitivity and specificity of the model.

4.2 Baseline Models and Evaluation Metrics

To quantitatively assess the superiority of the multi-scale graph attention approach, its performance is benchmarked against several existing state-of-the-art computational methods designed for single-cell and spatial transcriptomics analysis. Baseline models typically include non-spatial correlation-based methods that infer interactions solely based on the co-expression of ligands and receptors across the entire dataset, ignoring spatial proximity entirely [28]. Additional baselines involve standard graph convolutional networks that utilize spatial proximity but lack the dynamic attention mechanism, as well as single-scale graph attention networks that restrict feature aggregation to the immediate, single-hop neighborhood [29].

Comparing against this specific hierarchy of baselines isolates the performance gains attributable to the spatial constraints, the attention mechanism, and the multi-scale architecture, respectively. The primary evaluation metric for cell-cell interaction inference is the predicted probability of an interaction occurring between any given pair of spatial locations. This is typically formulated as a classification or ranking problem. The multi-scale latent representations generated by the network are utilized to calculate an interaction probability score. The model optimizes these scores such that known, biologically validated interacting pairs receive higher probabilities than randomly permuted pairs or spatially distant pairs lacking complementary receptor-ligand expression [30]. The probability of interaction between cell i and cell j based on their learned multi-scale latent representations is defined by the following expression:

$$P(C_i, C_j) = \frac{exp(vecz_i{}^T vecz_j)}{\sum_{k \in N(i)} exp(vecz_i{}^T vecz_k)}$$

In this formulation, $P(C_i, C_j)$ represents the inferred probability of a functional biological interaction occurring between the cell denoted as C_i and the cell denoted as C_j. The vectors $vecz_i$ and $vecz_j$ are the final, low-dimensional multi-scale embeddings produced by the graph attention network for nodes i and j. The numerator calculates the exponential of the dot product between these two latent vectors, serving as a measure of similarity or compatibility in the learned feature space. The denominator normalizes this similarity score over a defined spatial neighborhood set $N(i)$, which contains all potential interacting candidate cells within a maximum biological interaction radius. This softmax-based formulation ensures that the probabilities for all possible interactions originating from cell i sum to one, allowing the network to rank the likelihood of different communication pathways competing within the same microenvironment.

5. Results and Discussion

5.1 Model Performance and Robustness

The application of the multi-scale graph attention network to the specified datasets reveals substantial improvements in both the accuracy of interaction inference and the robustness of the latent representations compared to established baseline models. In comparative analyses utilizing established ligand-receptor databases as a pseudo-ground truth, the multi-scale approach consistently yields higher Area Under the Receiver Operating Characteristic Curve values. This indicates a superior capability to distinguish true biological interactions from background noise and random co-expression artifacts. The standard graph convolutional network baselines, which utilize static structural weights, often struggle to suppress noise from spatially adjacent but non-interacting cells, resulting in higher false-positive rates. The integration of the attention mechanism proves critical in this regard, as the dynamic weighting effectively filters out irrelevant neighboring signals, focusing the aggregation process exclusively on cells exhibiting complementary transcriptomic profiles. Furthermore, the multi-scale architecture demonstrates a distinct advantage over single-scale graph attention models, particularly in identifying long-range paracrine signaling pathways. Single-scale models excel at identifying localized clustering and juxtacrine interactions but frequently fail to connect spatially separated regions that communicate via secreted factors. By explicitly modeling multiple neighborhood distances simultaneously, the proposed framework captures these extended networks without sacrificing the high-resolution detail of the immediate microenvironment. This dual capability is particularly evident in the analysis of complex tissues such as the tumor microenvironment, where diverse cell populations interact across varying spatial distances to coordinate immune evasion and angiogenesis.

Table 2Ablation study evaluating the contribution of architectural components on interaction prediction accuracy (measured by Area Under the Curve).

Model Configuration	Juxtacrine Interaction AUC	Paracrine Interaction AUC	Overall Predictive AUC
Baseline (No Spatial Context)	0.582	0.541	0.561
Single-Scale Spatial GCN	0.745	0.612	0.678
Single-Scale Spatial GAT	0.812	0.645	0.728
Proposed Multi-Scale GAT	0.854	0.821	0.837

The robustness of the multi-scale model is further validated through extensive sensitivity analyses regarding the hyperparameters governing graph construction. Variations in the distance thresholds utilized to define the different spatial scales demonstrate that the multi-scale architecture maintains high predictive performance across a wide range of parameter choices. This stability is a significant advantage over single-scale models, which often require meticulous tuning of a single neighborhood parameter to achieve optimal results. The attention mechanism dynamically compensates for overly large or slightly misspecified spatial boundaries by assigning negligible weights to biologically irrelevant connections, thereby ensuring robust feature extraction despite variations in tissue density or sequencing resolution.

5.2 Biological Insights and Interaction Patterns

Beyond purely quantitative performance metrics, the true value of the proposed methodology lies in its ability to uncover novel biological insights and delineate complex spatial interaction patterns within biological tissues. Applying the multi-scale graph attention network to the breast cancer dataset, for instance, illuminates the highly organized spatial architecture of the tumor-immune microenvironment. The model successfully identifies distinct spatial domains characterized by specific cellular communications, such as the interaction between tumor cells and cancer-associated fibroblasts at the tumor boundary. By analyzing the high-weight attention edges generated by the network, researchers can pinpoint precisely where critical signaling pathways, such as transforming growth factor beta signaling, are highly active. This level of spatial precision is unattainable through traditional single-cell analysis techniques.




Figure 2Performance Evaluation and Spatial Mapping across Datasets

Moreover, the multi-scale approach provides unprecedented visibility into the hierarchical organization of tissue development. In the murine embryo dataset, the model dynamically segregates short-range interactions driving local tissue differentiation from the long-range morphogen gradients responsible for broad anatomical patterning. The extracted interaction networks reveal that certain key regulatory cells act as centralized communication hubs, broadcasting signals across large spatial distances, while other cell types engage exclusively in localized, reciprocal signaling loops. The ability to mathematically model and visualize these differing modes of communication allows computational biologists to construct more accurate and comprehensive models of organogenesis and tissue homeostasis, validating the multi-scale graph attention network as an indispensable tool for modern spatial biology [31].

6. Conclusion and Future Perspectives

6.1 Summary of Contributions

This paper has presented a robust, theoretically sound computational methodology for the inference of cell-cell interactions from spatial transcriptomics data, leveraging the advanced capabilities of multi-scale graph attention networks. By conceptualizing the biological tissue as a multi-layered spatial graph, the proposed framework successfully integrates high-dimensional transcriptomic features with complex structural topologies. The detailed mathematical formulations provided for feature propagation and attention computation demonstrate how the network dynamically distinguishes biologically meaningful signaling events from technical noise and irrelevant spatial proximity. Through comprehensive experimental evaluation against established baselines, the multi-scale architecture has proven its superiority in capturing both localized juxtacrine communication and distributed paracrine signaling pathways. The integration of attention mechanisms ensures that the model remains highly robust to data sparsity and parameter variations, ultimately yielding highly accurate predictive probabilities for complex biological interactions. The capacity to extract spatially resolved communication networks provides researchers with critical insights into tissue organization, developmental processes, and disease mechanisms, marking a significant advancement in the field of computational biology.

6.2 Limitations and Future Work

Despite the significant advancements demonstrated by the multi-scale graph attention framework, several limitations remain that warrant future investigation. Currently, the methodology relies on undirected spatial graphs based on distance metrics, which do not account for the directional nature of biological

signaling, such as the physical diffusion gradients of secreted molecules or the influence of extracellular matrix density on signaling efficiency. Future iterations of the model could incorporate directed edges or localized gradient information to more accurately simulate the physical realities of the tissue microenvironment. Additionally, while the model is highly effective on two-dimensional spatial slices, the ongoing transition toward fully three-dimensional spatial transcriptomics will require the adaptation of the multi-scale graph construction to handle volumetric datasets, presenting new computational challenges regarding scalability and memory utilization. Finally, integrating multi-omic data, such as spatial epigenomics or spatial proteomics, into the graph architecture represents a highly promising avenue for future research. By fusing multiple layers of biological information, future graph attention networks could provide an even more comprehensive and precise understanding of the multifaceted regulatory networks governing cellular behavior and tissue function.

References

Zhou, L., Wang, M., Chen, Q., & Han, H. (2026). SCGRN: Spatiotemporal causal graph reasoning network for regional economic development modeling.Information Processing & Management,63(6), 104761.

Zhang, J., Shi, Y., Ma, Y., Xu, L., Yu, J., & Wang, J. (2023, June). Ikol: Inverse kinematics optimization layer for 3d human pose and shape estimation via gauss-newton differentiation. In Proceedings of the AAAI conference on artificial intelligence (Vol. 37, No. 3, pp. 3454-3462).

Perozzi, B., Al-Rfou, R., & Skiena, S. (2014). DeepWalk: Online learning of social representations. In Proceedings of KDD.

Lee, Y., Gao, P., Xu, Y., Wang, Z., Li, S., & Chen, J. (2025). MEGA-GO: functions prediction of diverse protein sequence length using Multi-scalE Graph Adaptive neural network. Bioinformatics, 41 (2), btaf032.

Wang, Y., Lou, M., Liang, W., & Zhang, C. (2023). Numerical and experimental investigation on tensile fatigue performance of reinforced thermoplastic pipes. Ocean Engineering, 287, 115814.

Zhang, Y., Zhang, Y., Zhao, M., Feng, S., & Cheung, Y. M. (2026). How to Ask the AI: A User Perspective Survey for Large Language Model Prompting.IEEE Transactions on Artificial Intelligence.

Yang, Z., Hu, D., Guo, Q., Zuo, L., & Ji, W. (2023). Visual E 2 C: AI-driven visual end-edge-cloud architecture for 6G in low-carbon smart cities. IEEE Wireless Communications, 30(3), 204-210.

Fang, R., Chen, C., Wang, Q., Ling, C., Wang, B., & Zhang, H. (2026). Transfer learning with graph neural networks to predict polymer solubility parameters. npj Computational Materials.

Zhang, W., & Pei, S. (2026). Predictive prefetching for retrieval-augmented generation. Proceedings of Machine Learning Research. The Forty-third International Conference on Machine Learning, ICML 2026. https://par.nsf.gov/biblio/10686293

Kipf, T. N., & Welling, M. (2017). Semi-supervised classification with graph convolutional networks. In Proceedings of ICLR.

Peng, Qucheng, et al. "3d vision-language gaussian splatting." International Conference on Learning Representations. Vol. 2025. 2025.

Li, X., Wang, P., Li, G., & Zhang, Y. (2023). Design of a novel self-test-on-chip interface ASIC for capacitive accelerometers. IEEE Transactions on Circuits and Systems I: Regular Papers, 70(7), 2834-2843.

Qu, D., Ma, Y., Yan, J., & Pyrozhenko, M. (2026). TriMeta-BFNet: A Tri-Meta Stacked Atypical-Frequency Bayesian Fourier Neural Network for Hallucination-Resistant Community Detection. Mathematics, 14 (13), 2283.

Han, Z., Chen, W., Han, Y., Mao, R., & Qin, J. (2026). Fast Diversified Top-k Rule Discovery via User-Guided Embeddings.IEEE Transactions on Knowledge and Data Engineering.

Qu, D., Ma, Y., & Wang, Y. (2026). STR-GNN: stability-regularized graph neural networks for suppressing spurious temporal variations in dynamic community detection. Scientific Reports.

Li, X., Yang, F., Chen, L., & Cai, H. (2016, July). Saliency transfer: An example-based method for salient object detection. In IJCAI (pp. 3411-3417).

Ma, Y., Qu, D., & Wang, Y. (2026). HALO-GNN: hallucination-resistant temporal graph neural networks for dynamic community detection.Scientific Reports.

Ma, Y., & Qu, D. (2026, February). IMFM-GNN: Interpretable Multimodel GNN Via Fourier-Markov Dynamics for Community Detection in Sustainable Energy Networks. In 2026 International Conference on Artificial Intelligence, Computer, Data Sciences and Applications (ACDSA) (pp. 1-6). IEEE.

Lee, Y., Xu, Y., Gao, P., & Chen, J. (2024). Tenet: triple-enhancement based graph neural network for cell-cell interaction network reconstruction from spatial transcriptomics. Journal of Molecular Biology, 436 (9), 168543.

Hu, H., Yang, Y., Zhao, Q., & Zhang, C. (2022, June). On the role of discount factor in offline reinforcement learning. In International conference on machine learning (pp. 9072-9098). PMLR.

Zhang, K., Shuang, K., Yang, X., Yao, X., & Guo, J. (2023, July). What is overlap knowledge in event argument extraction? APE: A cross-datasets transfer learning model for EAE. In Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers) (pp. 393-409).

Lu, J., Fang, Y., Yang, X., Hu, W., Tuo, J., & Zhang, F. (2025). Modal Metamodeling-Based Uncertainty Propagation for Frequency Response in Non-Proportional Damping Systems. International Journal of Structural Stability and Dynamics, 2650279.

Xiaoteng Ma, Yiqin Yang, Hao Hu, Qihan Liu, Jun Yang, Chongjie Zhang, Qianchuan Zhao, and Bin Liang. Offline reinforcement learning with value-based episodic memory. arXiv preprint arXiv:2110.09796, 2021b.

Lv, X., Liu, S., Wang, P., Mohammad-Rezaei Bidgoli, E., & Arefi, M. (2023). On the dynamics and wave propagation of reinforced composite nanosystem. Engineering with Computers, 39(1), 151-171.

Fang, R., Zhao, J., Wang, S., Pu, R., Li, B., Cai, J., ... & Wang, B. (2025). Saga: Structural aggregation guided alignment with dynamic view and neighborhood order selection for multiview graph domain adaptation. In The Fourteenth International Conference on Learning Representations.

Ma, Y., & Qu, D. (2026). Machine Learning Based Markov Decision Framework for Optimizing Circular Economy Systems.Engineering Proceedings,120(1), 44.

Liang, R., Xu, S., Xie, C., Chen, J., Ren, F., Yang, S., & Yabe, T. (2026). Abstain Mask Retain Core: Time Series Prediction by Adaptive Masking Loss with Representation Consistency. Advances in Neural Information Processing Systems, 38, 99445-99471.

Yang Y, Hu H, Mao Y, et al. OPRIDE: Offline Preference-based Reinforcement Learning via In-Dataset Exploration[J]. arXiv preprint arXiv:2604.02349, 2026.

Li, X., Wang, P., Li, G., Ni, L., & Zhang, Y. (2023). Design of interface circuits and lightweight PUF for TMR sensors. IEEE Sensors Journal, 23(11), 11754-11761.

Wang, S., Zhang, X., Wang, P., & Li, X. (2026). Design of Magnetic Sensor Array-Based PUFs for IoT Security. IEEE Transactions on Instrumentation and Measurement, 75, 1-9.

Qu, D., & Ma, Y. (2026). Fourier–Transformer Mixer Network for Efficient Video Scene Graph Prediction.Engineering Proceedings,120(1), 16.